

### HEAVY DUTY SCRAPER™

### Textile mats for entrance flooring solutions

Product description	Tufted cut pile manufactured with twisted and heat set BCF polyamide 6 monofilaments on nitrile rubber backing		
	Fire resistance	Dfl-s1	
	Total thickness	10mm	
	Total Weight	2880g/m <sup>2</sup> (+/- 5%)	
Yarn	Composition	100% Econyl ® regenerated BCF polyamide twisted and heat set monofilaments	
Primary Backing	Composition and construction	Polyester nonwoven	
Pile	Construction	Cut pile	
	Tuft method	Straight tufted	
	Pile height	11mm	
	Stitch rate	4.3 spi	
	Total fabric weight	780g/m <sup>2</sup>	
Textile Colour Fastness	Dyeing Method	Solution dyed	
	Light	8 (maximum mark)	(ISO 105-B02)
Secondary Backing	Composition	100% Nitrile Rubber	
	Mass	1905g/m <sup>2</sup> (body of mat)	
	Backing thickness	1.5mm	
	Border thickness	2.8mm	
	Border width	20mm	
Performance Testing	Antistatic Behaviour	Approx 10 <sup>11</sup> ohms	(ISO 10965)
	Personal Charging	<2kV (antistatic)	(ISO 6356)
	Flammability	Dfl-s1	(EN ISO 13501)
	Slip Resistance	To be confirmed	(EN 13893)
Size	85 x 150cm		
	85 x 300cm		
	115 x 200cm		
ADA / BS 8300 / ISO 21542 Compliant		Yes	
LEED® Point Contributor		Yes	
ISO Manufacturing Certification		ISO 9001	
ISO Environmental Certification		ISO 14001	
Origin		EU	
Warranty		Please refer to our written warranty	

Please Note: As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/ labelling /processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Each customer must test and be responsible for its own specific use, further processing, labelling, marketing, etc. All sales are exclusively subject to our standard terms of sales posted at [www.milliken.com/terms](http://www.milliken.com/terms) (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing.